

# MERCURY HD-30 DL, HD-30 FLEX

30" Dual-Brush, Battery-Powered Walk-Behind Autoscrubbers

The HD-30 Models are the NEW, 30-inch, battery-powered, dual-brush, TSM Inc. designed, walk-behind autoscrubbers from MERCURY.



- The strong, welded chassis holds modular components - switch boxes, pumps, tanks, scrub heads, pump sets and drive motors.



- HD-30 DL model is built with 18.5 gallon, stainless steel solution and recovery tanks and with manual squeegee controls. The FLEX model uses 26.5 gallon tanks and automatic squeegee control for even greater productivity.



- Operating controls are easy to learn for the novice user.
- Solution tank fills through filter-protected funnel opening in the low rise cover.



- Tip the hood forward hood and lift the modular vacuum unit for easy access to the 36 V battery set.

- A modular scrub head mounts with plug-in connection. Modular pump, motor, and control assemblies give fast, easy maintenance.



- Select a 15.5" diameter brush set in poly, nylon, bassine or grit bristle to scrub a range of floors and soils. Lug mount design is engineered for hands-free brush mounting.

- Variable brush down-pressure easily adjusts for lightest to most aggressive scrubbing. Offset brush for easy scrubbing close to walls.

- 3 year warranty on pumps and motors.

Almost indestructible 30" walk-behind autoscrubber with 18.5 or 26.5 gallon capacity tanks



## SPECIFICATIONS

Model	HD-30DL	HD-30 FLEX
Scrub Path	29.5" (75 cm)	29.5" (75 cm)
Squeegee Width	37.5" (95 cm)	37.5" (95 cm)
Productivity	30 msf / hour	35 msf / hour
Solution Tank	18.5 gal (70 L)	26.5 gal (100L)
Recovery Tank	18.5 gal (70 L)	26.5 gal (100L)
Brush size	(2) 15.5" disk	(2) 15.5" disk
Brush motor	(2) 200 watt	(2) 200 watt
Brush pressure	0-110 lbs	0-110 lbs
Traction motor	0.55 HP	0.55 HP
Vacuum motor	0.75 HP	0.75 HP
Battery Set	36 DCV (3-12 V) / 210 Amp	36 DCV (3-12 V) / 210 Amp
Weight (w/o batteries)	462 lbs	539 lbs
Warranty	1 years	1 years



110 South Van Brunt Street  
Englewood, NJ 07631  
www.mercuryfloormachines.com

Phone (201) 568-4606  
Toll Free (888) 568-4606  
FAX (201) 568-7962